





# CERTIFICATE OF APPROVAL


## **Product Conformity Certification**

This is to certify that

### Thai Wire Products Public Co. Ltd.

at

## 4 I-5 RD. Maptaphud Industrial Estate Maptaphut, Muang Rayong Thailand 21150



### **SCOPE OF CERTIFICATION**

### Steel Prestressing Wire and Strand Manufacture to AS/NZS 4672:2007

Products listed on this certificate may be supplied under ACRS certification only where supplied for installation directly by this certificate holder or supplied by an ACRS Traceability Scheme Certified Supplier with a Scope of Certification including this material.

This certificate remains the property of the Authority and is issued subject to the Regulations of the Authority.

| CERTIFICATE NUMBER | VERSION | FIRST APPROVAL   | ISSUE DATE      | EXPIRY DATE      |
|--------------------|---------|------------------|-----------------|------------------|
| 161201             | 1       | 16 December 2016 | 01 January 2025 | 31 December 2025 |

SIGNED FOR ACRS

Andrew Wheeler,

**Executive Director** 

AUSTRALASIAN CERTIFICATION AUTHORITY FOR REINFORCING AND STRUCTURAL STEELS LTD | ABN: 40 096 692 545 | PO BOX 1369, CROWS NEST NSW 1585, AUSTRALIA

To check the validity of this certificate please scan the above Static QR Code with the ACRS Cloud App or visit www.steelcertification.com

Cert. Ref.: 041-02 161201









# **CERTIFICATE OF APPROVAL**

## **Product Conformity Certification**

Certificate No: 161201
Thai Wire Products Public Co. Ltd.

at

4 I-5 RD. Maptaphud Industrial Estate Maptaphut, Muang Rayong Thailand 21150



### Products assessed by ACRS to the following Standards:

#### AS/NZS 4672 Prestressing Wire & Strand

- Stress Relieved Wire 5.03 mm 1700 MPa Relax 2 Certified Line: 3
- AS/NZS 4672 Strand 7 Wire Ordinary 9.5 mm 1850 MPa Relax 2 Certified Line: 3
- AS/NZS 4672 Strand 7 Wire Ordinary 12.7 mm 1870 MPa Relax 2 Certified Line: 1 & 2
- AS/NZS 4672 Strand 7 Wire Ordinary 15.2 mm\* 1860 MPa Relax 2 Certified Line: 1 & 2

(\*) The strength requirements of the 15.2 mm 1860 MPa grade also meet the strength requirements of 15.2 mm 1830 MPa and 15.2 mm 1750 MPa grades. Confirmation is required on Nominal Cross Sectional Area and Nominal Mass per Length.

#### **Approved Company Information**

Tag

| STANDARD TO AS/NZS 4672.1-2007 | SIZE : 12.70 mm. | AS/NZS 4672.1-7 Wire ordinary-12.7-1870-Relax 2-Right | COIL NO. : 62013\_0055 - 0311 | MODIFICATION : 0.080212066 | NET WITE PRODUCTS PUBLIC COMPANY LIMITED | NET WT. : 3,080 kgs. | LENGTH : 3,958 m. | MODIFICATION : 0.080212066 | LENGTH : 3,958 m. | LENGTH : 3,958 m. | MODIFICATION : 0.080212066 | LENGTH : 3,080 kgs. | LENGTH : 3,080 kgs.

To check the validity of this certificate please scan the above Static QR Code with the ACRS Cloud App or visit www.steelcertification.com

Cert. Ref.: 041-02 161201

